



SOKYMAT

**InLine UHF Tag
EPC Gen2 915 MHz
ISO 18000**

| | | | |
|---------------------|--|----------------------|------------------------------|
| Chip type: | EPC Gen2 – Read / Write 512bits | | *Test conditions and remarks |
| Physical: | Length: | 230 mm ± 2 mm | |
| | Thickness: | 15.0 mm ± 0.5 mm | |
| | Width: | 15.0 mm ± 0.5 mm | |
| | Weight: | 35 g | |
| | Material: | PC / ABS High Impact | |
| | Color: | Light gray | |
| Electrical: | Operating frequency: | 915 MHz | *At room temperature |
| | | | |
| Chemical: | Water immersion IP 67 | | *20°C, 35min, 1m |
| | Resistant to mineral acids and to large number of organics acids aqueous saline solution | | |
| | | | |
| Thermal: | Storage: | -40°C to +85°C | * 1x 1000h |
| | Operating: | -40°C to +85°C | |
| | | | |
| Part number: | 656903 | | |

© HID reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. HID declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.3.150 - V1 - DefKey: 3312895 - 28.10.2008 - Page: 1 of 1